

10/24/00

354 U.S. PAT. & TM. OFF.

UTILITY PATENT APPLICATION TRANSMITTAL

Only for nonprovisional applications under 37 CFR § 1.53(b)

Attorney Docket No.

CROSS1400-1

First Inventor or Application Identifier

Michael A. Nelson, et al.

Title

System and Method for Storing Frame Header Data

Express Mail Label No.

EL562561684US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 202311. ☒ Fee Transmittal for FY 2000
(Submit an original and a duplicate for fee processing)2. ☒ Specification [Total Pages] **27**
(preferred arrangement set forth below)

- x - Descriptive Title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- x - Background of the Invention
- x - Brief Summary of the Invention
- x - Brief Description of the Drawings (if filed)
- x - Detailed Description
- x - Claim(s)
- x - Abstract of the Disclosure

3. ☒ Drawing(s) (35 USC 113) [Total Sheets] **6**4. Oath or Declaration [Total Pages] **X**

- a. ☒ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)

5. ☐ Incorporation By Reference (useable if box 4b is checked). The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

- 6. ☐ Microfiche Computer Program (Appendix)
- 7. Nucleotide and Amino Acid Sequence Information (if applicable, all necessary)
 - a. ☐ Computer-Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

- 8. ☒ Assignment Papers (cover sheet & document(s))
- 9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney
- 10. ☐ English Translation Document (if applicable)
- 11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
- 12. ☐ Preliminary Amendment
- 13. ☒ Return Receipt Postcard
- 14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired
- 15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
- 16. ☒ Other: Certificate of Express Mail
Check

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information below and in a preliminary amendment

☐ Continuation ☐ Divisional ☐ Continuation-In-Part (CIP) of prior Application No.: _____

Prior application information: Examiner _____ Group / Art Unit _____

☒ Claims the benefit of Provisional Application No. 60/202,836; Filed 05/08/00

CORRESPONDENCE ADDRESS:

Customer Number Label:

Name: Mark L. Berrier

Ph: 512-457-7016

Fax: 512-457-7070

TYPED or PRINTED NAME Mark L. BerrierREGISTRATION NO. 35,066

SIGNATURE

Date

10/24/00

FEE TRANSMITTAL for FY 2000

Patent fees are subject to annual revision.
Small Entity payments must be supported by a small entity
statement, otherwise large entity fees must be paid.

Complete if Known

Application Number	
Filing Date	
First Named Inventor	Michael A. Nelson, et al.
Examiner Name	
Group / Art Unit	
Attorney Docket No.	CROSS1400-1

TOTAL AMOUNT OF PAYMENT (\$ 784.00)

PC926 U.S. PTO
09/695755
10/24/00

METHOD OF PAYMENT (check one)

1. ☐ The Commissioner is hereby authorized to charge indicated fees and credit any over payments to:

Deposit Account Number

50-0456

Deposit Account Name

Gray Cary Ware & Freidenrich LLP

☒

Charge Any Additional Fee Required Under 37 CFR §§ 1.16 and 1.17

2. ☒ Payment Enclosed:

☒

Check

☐

Money Order

☐

Other

FEE CALCULATION

1. BASIC FILING FEE

Large Entity

Small Entity

Code	\$	Code	\$	Fee Description	Fee Paid
101	690	201	345	Utility Filing Fee	690
106	310	206	155	Design Filing Fee	
107	480	207	240	Plant Filing Fee	
108	690	208	345	Reissue Filing Fee	
114	150	214	75	Provisional Filing Fee	

SUBTOTAL (1)

(\$ 690.00)

2. EXTRA CLAIM FEES

Claims	Extra Claims X	Fee from below =	Fee Paid
23	3	18.00	54
Ind. Clms 3	0	78.00	0
Multiple Dependent Claims			

Large Entity

Small Entity

Code	\$	Code	\$	Fee Description
103	18	203	9	Claims in excess of 20
102	78	202	39	Indep. claims in excess of 3
104	260	204	130	Multiple dependent claim
109	78	209	39	Reissue indep. claims over original patent
110	18	210	9	Reissue claims in excess of 20 and over original patent

SUBTOTAL (2)

(\$ 54.00)

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity

Small Entity

Code	\$	Code	\$	Fee Description	Fee Paid
105	130	205	65	Surchrgr - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	
147	2520	147	2520	Filing a request for reexamination	
112	920*	112	920*	Request publication of SIR prior to Examiner action	
113	1840*	113	1840*	Request publication of SIR prior to Examiner action	
115	110	215	55	Extension for reply within first month	
116	380	216	190	Extension for reply within second month	
117	870	217	435	Extension for reply within third month	
118	1360	218	680	Extension for reply within fourth month	
119	300	219	150	Notice of Appeal	
120	300	220	150	Filing a brief in support of appeal	
121	260	221	130	Request for oral hearing	
138	1510	138	1510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive: unavoidable	
141	1210	241	605	Petition to revive: unintentional	
142	1210	242	605	Utility issue fee (or reissue)	
143	430	243	215	Design issue fee	
144	580	244	290	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Petitions related to provisional applications	
126	240	126	240	Submission of Information Disclosure Statement	
581	40	581	40	Recording each patent assignment per property	40
146	690	246	345	Filing a submission after final rejection (37 CFR § 1.129(a))	
149	690	249	345	Each additional invention to be examined (37 CFR § 1.129(b))	

Other fee (specify) _____

Other fee (specify) _____

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3)

(\$ 40.00)

SUBMITTED BY:

Name Mark L. Berrier, Reg. No. 35,066

Customer No.

25094

Complete (if applicable)

Telephone

(512) 457-7000

Signature

Date

October 24, 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Atty Docket No. (Optional)

CROSS1400-1

Attn: Box Patent Application
Hon. Asst. Commissioner of Patents
Washington, D.C. 20231

In the Application of:
Michael A. Nelson, et al.

Date Filed:
October 24, 2000

Title:
System and Method for Storing Frame
Header Data



Sir:

I hereby certify that the enclosures listed below are being deposited with the United States Postal Service "EXPRESS MAIL Post Office to Addressee" service under 37 C.F.R. § 1.10, Mailing Label Certificate No. EL562561684, on October 24, 2000, addressed to Box Patent Application, Assistant Commissioner for Patents, Washington, DC 20231.

Respectfully submitted,

GRAY CARY WARE ▲ FREIDENRICH LLP

Kerry Thornhill

Enclosures:

Postcard
Check for \$744.00
Utility Patent Application Transmittal
Fee Transmittal of FY 2000
Specification, 23 Claims, Abstract (28 pages)
4 Sheets of Drawings (Figures 1-4b)
Declaration and Power of Attorney
Form PTO-1595
Assignment
Check for \$40.00 Assignment Recordation Fee

004304 03 23 2000

SYSTEM AND METHOD FOR STORING FRAME HEADER DATA

FIELD OF THE INVENTION

5 The invention relates generally to data
communication in computer systems, and more particularly to a
system and method implemented in connection with packet
switching protocols wherein packet (frame) header information
10 is stored in a buffer separate from the corresponding packet
buffer to allow routing decisions to be made based on the
header information without reading the packet out of the
buffer.

5 BACKGROUND OF THE INVENTION

Individual computer systems can be combined to form
networks. There are many different types of networks,
including local area networks (LANs,) wide area networks
20 (WANs,) storage area networks (SANs) and many others.
Networks are typically characterized by several
characteristics, including their protocols, their
architectures and their topologies.

25 Networks may be configured in various topologies,
such as rings or loops, point-to-point connections or
switched networks. Switched networks use a set of
interconnected switches to establish data paths between
several computers or other devices. Typically, devices
30 connected to a switched network will format data to be
transmitted between them into packets, or frames, which are
then routed through the network. The frames include data

- 2 -

which is used to transport them from a source to a destination (i.e., header information) as well as the data which the source wishes to send to the destination.

5 Referring to Fig. 1, a flow diagram illustrating the process by which frames are routed through a switch is shown. When a frame is received by a particular switch, The switch typically stores the frame (including the corresponding header) in a buffer until it can be sent to another device.
10 This device may be the destination device or an intermediate device which will route the frame to another switch or to the destination device. This buffer is normally a first-in-first-out (FIFO) buffer. When a frame reaches the head of the FIFO buffer, it can be routed (transmitted) by the switch. In
15 order for the switch to make a routing decision for the frame, it must examine the frame's header to obtain the corresponding transport information. Because the transport information is stored only in the header of the frame which is in the FIFO, at least part of the frame must be read out of the FIFO so
20 that the transport information can be read. The information which is read out of the FIFO must then be stored while the routing decision is made. Only after the routing decision has been made can the frame be routed by the switch. Because the frame must be read from the FIFO and stored in the second
25 location while the routing decision is made, the latency of the frame's transport from the source device to the destination device is increased.

SUMMARY OF THE INVENTION

One or more of the problems outlined above may be solved by the various embodiments of the present invention which, broadly speaking, comprises a system and method for storing header information in parallel with corresponding packets or frames of data, wherein the frames of data are stored in a first-in-first-out buffer and wherein the header information is accessed to make routing decisions in order to avoid having to read the frames out of the buffer.

In one embodiment, the invention comprises a buffer system implemented in each port of a network switch. Receive logic in the port stores frames of data in the storage elements of a FIFO buffer and concurrently snoops on the frame data to obtain header information. The header information is stored in a buffer separate from the FIFO that stores the frames. The header information can be read from the header buffer rather than the frame buffer. This eliminates the need to read a portion of the frame out of the FIFO and store this information in another buffer while a routing decision is made. It also allows the routing decision to be made before the second buffer becomes available. A timer may also be associated with each header in the header buffer so that it can be determined when frames are stale and must be discarded.

In another embodiment, the invention comprises a method wherein when frames first arrive at a port, the frames are "snooped" (i.e., examined) and the information in the header field is copied to a frame header register. At the same time, a timer associated with the header entry is

started. This timer continues to run while the header and the frame are stored in their respective buffers. When the time comes to forward the frame at the head of the FIFO, the header register and timer are examined and the routing decision made.

5 As that frame is being read out of the FIFO, the header corresponding to the next frame is examined, so the routing decision for the second frame can be made before the first frame has been completely read out of the FIFO.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and advantages of the invention may become apparent upon reading the following detailed
5 description and upon reference to the accompanying drawings in which:

Fig. 1 is a flow diagram illustrating the process by which frames are routed through a switch;

Fig. 2 is a diagram illustrating the interconnection of a plurality of devices via a fibre channel fabric in one embodiment;

Fig. 3 is a block diagram illustrating the structure of a frame of data in one embodiment;

Fig. 4 is a block diagram illustrating the manner in which frames of data are buffered in one embodiment;

Fig. 5 is a block diagram illustrating an embodiment of the present system which includes timers corresponding to the frame and header information;

Fig. 6 is a flow diagram illustrating a method for storing received frames in a frame FIFO and copying header data for the frames in a header FIFO in one embodiment;

Fig. 7 is a flow diagram illustrating a method for moving frames from a FIFO to a transmit buffer and

transmitting the frames to a subsequent port in one embodiment.

While the invention is subject to various
5 modifications and alternative forms, specific embodiments
thereof are shown by way of example in the drawings and the
accompanying detailed description. It should be understood,
however, that the drawings and detailed description are not
intended to limit the invention to the particular embodiment
10 which is described. This disclosure is instead intended to
cover all modifications, equivalents and alternatives falling
within the spirit and scope of the present invention as
defined by the appended claims.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A preferred embodiment of the invention is described below. It should be noted that this embodiment and other
5 embodiments described below are exemplary and are intended to be illustrative of the invention rather than limiting.

In one embodiment, the invention comprises a buffer system wherein header information is stored in a buffer
10 separate from the FIFO that stores the frame itself. The header information can be read from the header buffer rather than the frame buffer. This eliminates the need to read part of the frame out of the FIFO and store this data in another buffer while a routing decision is made. A timer may also be
5 associated with each header in the header buffer so that it can be determined when frames are stale and must be discarded.

In another embodiment, the invention comprises a method wherein when frames first arrive at a port, the frames
20 are "snooped" (i.e., examined) and the information in the header field is copied to a frame header register. At the same time, a timer associated with the header entry is started. This timer continues to run while the header and the frame are stored in their respective buffers. When the time
25 comes to forward the frame at the head of the FIFO, the header register and timer are examined and the routing decision made. ("Forward" as used here refers to the transmission of the frame along the next leg of its journey to the destination device.) As that frame is being read out of the FIFO, the
30 header corresponding to the next frame is examined, so the

routing decision for the second frame can be made before the first frame has been completely read out of the FIFO.

5 The invention may provide a number of advantages over the prior art. For example, since each frame does not need to be read out of the FIFO and stored in another buffer while the routing decision for the frame is made, the latency of the frame's transport may be reduced. The amount of logic required in the system may also be reduced by eliminating this
10 step. Still further, a routing decision can be made before the frame is ready to be transmitted, so the throughput of the system may be increased.

15 In one embodiment, the present system is implemented in a Fibre Channel switch. "Fibre Channel" refers to an data communication technology, as well as a set of standards being developed by the American National Standards Institute (ANSI) to define the technology. Fibre Channel supports both shared media and dedicated, or switched, media. Fibre Channel can be
20 used to provide means for data transfer in many different systems, supporting workstation clusters, switched LANs, SANs (storage area networks) and the like.

25 Despite its name, "Fibre Channel" technology is not strictly a channel-oriented technology, nor does it represent a network topology. Fibre Channel allows devices to be interconnected in a more generalized scheme. In this scheme, devices may be connected by fibre channel links in several configurations, including point-to-point and loop
30 configurations, as well as what is referred to as a "fabric." The fabric is formed by one or more interconnected Fibre

Channel links and switches. Devices can then be interconnected through the fabric. The fabric may be a circuit switch, an active hub or a loop. These devices may be cascaded together to increase the number of available ports in the fabric.

Each Fibre Channel link consists of a pair of unidirectional fibers. Each fiber is connected to an associated transmitter and receiver. The link is connected between a pair of data ports. Data is transmitted from a first one of the ports to a second one of the ports over a first one of the fibers (and the corresponding transmitter and receiver.) Data which is transmitted from the second port to the first port is carried on the second fiber. The transmitters and receivers are managed by controllers at the respective ports.

As noted above, the Fibre Channel fabric may include one or more interconnected switches. Referring to Fig. 2, a diagram illustrating the interconnection of a plurality of sites, or devices, via a Fibre Channel fabric is shown. Each of the switches 12 which together form fabric 10 is configured to receive and buffer frames of data from a source (in this case, 14c), to make routing decisions for the frames, and to transmit the frames to the appropriate destination (in this case, 14e). In the system illustrated in Fig. 2, frames are shown being routed from site 14c, through switch 12c, then through switch 12b, and finally to destination site 14e. Each switch has at least two ports and typically has a maximum of 16 ports (although this may vary.) Each of the ports in a Fibre Channel switch has a receive fibre and a transmit fibre.

Normally, frames are received at one of the ports and are transmitted to another one of the ports within the switch.

It should be noted that, for the purposes of this disclosure, identical items in the figures may be indicated by identical reference numerals followed by a lowercase letter, e.g., 12a, 12b, and so on. The items may be collectively referred to herein simply by the reference numeral.

Referring to Fig. 3, a block diagram illustrating the structure of a frame in one embodiment is shown. In this embodiment, each frame includes a start-of-frame (SOF) primitive 20, a header 22, data 24, and an end-of-frame (EOF) primitive 26. SOF primitive 20 identifies the beginning of a frame. EOF primitive 26 similarly serves to identify the end of the frame. All of the data of a frame, whether useful data or overhead data, is enclosed between the SOF and EOF primitives. Header 22 comprises overhead data related to the frame. In particular, Header 22 includes information identifying the destination of the frame. The destination information is used by the switches to make the routing decisions necessary to deliver the frame to the target site or device. Data 24 comprises useful data. In other words, data 24 is the data which the was originally intended to be delivered from the source to the destination.

Referring to Fig. 4, a block diagram illustrating the manner in which frames of data are buffered in one embodiment is shown. Data which is received at a port is examined for the SOF primitive which identifies the beginning of a frame. When the SOF primitive is detected, the port

5 makes a decision to store the corresponding frame in a frame
FIFO 30 of the port. The frame (i.e., all of the data
received by the port, from the SOF primitive up to and
including the EOF primitive) is stored in one of the storage
locations 31 in FIFO 30. Frames are read out of FIFO 30 and
transmitted in the order in which they were written to the
FIFO. The frame which has been in FIFO 30 for the longest
time is at the head 31e of the FIFO and is the next frame to
be read out. The frame which has been in FIFO 30 for the
shortest time is at the tail 31a of the FIFO. All of the other
frames in the FIFO will be read out before this frame. When
the port is ready to transmit one of the frames to another
port, it moves the frame at the head 31e of FIFO 30 to a
transmit buffer in the other port. (This assumes that the
other port has a transmit buffer. It should be noted that a
transmit buffer is not required at the destination port.)

20 In addition to frame buffer 30, the port includes a
header buffer 34. As described above, the SOF primitive
signals the beginning of a frame and is followed by the frame
header. The port snoops on the received data and, as the
header is received, the port copies the header to a FIFO which
serves as header buffer 34. (The port may alternately copy
only selected routing information to header buffer 34.) The
headers of the received frames are stored in storage locations
35 within header buffer 34, with the oldest entry at the head
35e of header buffer 34 and the newest entry at the tail 35a
of header buffer 34. When the port is ready to make a routing
decision for one of the frames in frame buffer 30, the
corresponding header is read out of header buffer 34.

5 The headers stored in header buffer 34 roughly
correspond to the frames stored in frame buffer 30. That is,
there is normally a one-to-one correspondence between the
frames and the headers. If header buffer 34 comprises a
destructive FIFO, then a header register (not shown) is used
to hold the header that would otherwise reside at the head of
header buffer 34. This is because the header in this position
needs to be retained after it is read, which is not possible
with a destructive FIFO alone. (The header register may also
10 need to be used in some implementations which store the
headers in RAM.) If header buffer 34 comprises a set of
registers, the header in position 35e can be read non-
destructively.

15 The header corresponding to the frame at the head of
the frame buffer is read to determine the destination port to
which the frame will be sent. Because the header can be read
from header buffer 34 (or a subsequent header register,) the
port can potentially make a routing decision for the frame
before it is ready to be transmitted. When the frame at the
head of FIFO 30 is moved to the destination port, the
subsequent frame is moved to the head of FIFO 30 and the
header corresponding to the subsequent frame is moved to the
head of header buffer 34 so that a routing decision can be
25 made for the subsequent frame. The present system thus
overlaps the routing decision for a frame with the
transmission of the preceding frame, thereby reducing the
latency in transporting the frames through the port.

30 In prior art systems, the routing decision for the
frame in the frame buffer was made when the frame was ready to

be transmitted to the transmit buffer of the destination port. Consequently, a routing decision for the subsequent frame could not be made until the previous frame had been transmitted to its destination port. In the present system, the header information for a frame can be accessed before the frame comes to the head of the frame buffer. Accordingly, when the frame comes to the head of the frame buffer, it can immediately be transferred to the appropriate transmit buffer according to the routing decision that was made while it was still being promoted through the frame buffer. This eliminates the delay of making the routing decision after the frame header can be read out of the frame buffer. (It should be noted that the transmit buffer may have an associated timer which is used to enforce rules regarding the discarding of frames that become stale in the transmit buffer.)

In one embodiment, the system uses register elements to store the header information. The header register elements each comprise a chain of cascaded flip-flops, timers, and controllers which is sufficiently large to hold a frame header. The header register has enough locations to match the number of frames the FIFO can hold. Each location is aware if it holds an entry that has not been processed yet, and if the entry in the previous location (newer entries) has been processed (utilizing a VALID state flag). If a location has an entry that has been processed (VALID flag false) and the previous location has an unprocessed location (VALID flag true), then information is loaded from the previous location to the current location, the VALID flag for the previous location is marked as false, and the VALID flag for the current location is marked as true.

In another embodiment, dual port RAM can be used to store the header information. While RAM implementations do not have the same physical first-in-first-out constraints of FIFO memory devices, the same operation can be achieved using pointer manipulation. Headers in the RAM are accessed in a circular manner with read and write pointers. Rather than promoting information from one storage element to the next, the read and write pointers are advanced. It should be noted that the frame FIFO can also be implemented using these different types of memory elements. The present system may provide advantages in a RAM implementation as well as a FIFO implementation because it may reduce the need for some of the pointer manipulation which is used to achieve the first-in-first-out behavior.

The header buffer has a set of timers that are started when corresponding entries are made in the header buffer. The header for each frame has its own timer. Just like the data, the timer information is promoted from one stage to the next. If a timer increment would occur simultaneously with a timer promotion, the promotion is held off until after the timer has been incremented (so the increment is not lost). Since the header information is stored in the header buffer at the same time the frame is stored in the FIFO, the timers can be used to determine how long each frame has been in the buffer. This is necessary because the switch in this embodiment is assumed to implement rules which must be enforced regarding the aging of frames. For example, frames may not be allowed to remain in the buffer for more than one second. If the timer for a particular

header, hence a particular frame, indicates that the header and frame have been stored for more than one second, the frame is discarded rather than being transmitted when it reaches the head of the buffer.

5

It is contemplated that various methods can be used to store timer information. For example, when using register storage elements, cascaded pre-loadable counters can be used. These counters can forward the count for each of the frames/headers from one stage to the next. For RAM based storage of header information, resettable but not loadable counters can be used. A specific counter can be configured to hold the count for a frame/header for the entire time the information is valid, rather than promoting counts through stages. Another method uses less resources, but requires a more complicated controller. This method stores the count value in RAM along with the routing information (utilizing unused RAM locations). When it is time to increment the timers (approximately every 100 milliseconds) a circuit reads the current count, adds one to it, and rewrites the new value to RAM. An arbiter circuit can give top priority to writing and reading the routing information. The adder state machine can be paused when it is time to read or write routing information, and then resumed.

10

15

20

25

Referring to Fig. 5, a block diagram illustrating an embodiment of the present system which includes timers corresponding to the frame and header information is shown. In this figure, data which is transmitted to a port is received by receive logic 40. Receive logic 40 is configured to detect the SOF and EOF primitives which define the

30

boundaries of frames in the received data and to store individual frames to locations in frame FIFO 42. Receive logic 40 includes circuitry to snoop on the received data and to copy the header of each frame to header FIFO 44. The copying of a header to header FIFO 44 occurs in parallel with the storage of the corresponding frame in frame FIFO 42. When a header is copied to header FIFO 44, a corresponding timer 45 is started. (While there is a separate timer for each header, a single timer block is shown in the figure.)

The frames, headers and timers are promoted through the storage locations of their respective storage buffers. The header at the head of header FIFO 44 is read by transfer logic 46 and a routing decision for the corresponding frame in frame FIFO 42 is made. When the frame reaches the head of frame FIFO 42, it is routed by transfer logic 46 to transmit buffer 47 if the FIFO is available. Transfer logic 46 is configured to read the value of the timer corresponding to the header at the head of header FIFO 44. If the timer has exceeded the predetermined maximum value, the corresponding header and frame are discarded. Otherwise, they are transferred normally to the transmit FIFO. (As explained above, the header and frame are discarded because they have become stale.) When the header and frame are either discarded or transferred to the transmit buffer 47 (and corresponding header register 48,) the frames, headers and timers are promoted through in the receive buffers (frame and header FIFOs.)

Transfer logic 46 is configured to make routing decisions for the frames that are received by a port.

Transfer logic 46 reads the frame at the head of receive buffer 42 and transmits it to another port. The routing decision for this frame is made by transfer logic 46 before the frame reaches transmit buffer 47. While the frame is being moved from the receive FIFO 42 to the transmit buffer 47, transfer logic 46 examines the next header in FIFO 44 and makes a routing decision for the corresponding frame in receive FIFO 42.

The header buffer system can be implemented in the destination port as well as the receive port. Thus, while one frame is being transmitted from transmit buffer 47, the header for the next frame can be transferred to header register 49, where it can be examined by transmit logic 50 in preparation for transmitting the corresponding frame.

It should be noted that a header bypass scheme can be implemented in the present system. If the header buffer is empty, new entries may have to be promoted through the sequential storage locations of the header buffer before reaching the head of the buffer and becoming available to move into the transmit header register. This adds unnecessary latency to the transport of the frames through the port. Bypass logic can be added to the system to move the headers immediately to the head of the header buffer.

Referring to Figs. 6 and 7, flow diagrams illustrating the method implemented in one embodiment of the present system is shown. Fig 6 illustrates the initial stage of the process. As shown in the figure, frames are received at the port. When an SOF primitive is identified, the

primitive and the frame which follows are stored in the frame
FIFO. At the same time, the received data is snooped to
identify header data. The header for the frame is copied and
stored to the header FIFO. When an EOF primitive is detected,
5 receipt of the frame by the port is complete. This portion of
the process is repeated as more data is received.

Referring to Fig. 7, another part of the process
that occurs subsequent to the storing of a frame and
10 corresponding header in the buffers of the receive port is
illustrated. In this figure, the process includes two sets of
operations which occur substantially in parallel. The left
side of the figure illustrates the transport of frames from
the frame buffer of the receive port to the transmit buffer of
15 the transmit port and the subsequent transmission of the
frames. The right side of the figure illustrates the movement
of header information to the head of the header buffer (and
the subsequent routing decision) and the transfer of the
header to the header register (and the corresponding transmit
20 decision.)

First, the header information reaches the head of
the header buffer. This information is used to make a routing
decision for the corresponding frame. The frame may not have
25 reached the head of the frame buffer yet because the previous
frame may be in the process of being transferred to the
transmit buffer of a transmit port. The header information is
nevertheless available to be used for the routing decision.
After the routing decision has been made, and after the frame
30 reaches the head of the frame buffer, the frame can be
transferred to the appropriate transmit buffer. When the

frame is transferred, the corresponding header information is transferred to the header register of the transmit port. The header information can then be read from the header register if necessary to make a routing decision for the transmission of the frame from the transmit buffer. The frame is then transmitted from the transmit buffer. It should be noted that, while Fig. 7 suggests that certain ones of the depicted steps may occur before others, these relationships do not necessarily apply to all implementations of the present system and method.

While the present invention has been described with reference to particular embodiments, it should be understood that the embodiments are illustrative and that the scope of the invention is not limited to these embodiments. Many variations, modifications, additions and improvements to the embodiments described above are possible. It is contemplated that these variations, modifications, additions and improvements fall within the scope of the invention as detailed within the following claims.

CLAIMS

What is claimed is:

- 5 1. A method comprising:
 receiving a plurality of frames;
 storing the frames in a receive buffer, wherein the
 receive buffer is configured to be accessed in a
 first-in-first-out fashion;
10 storing header information corresponding to each of the
 frames in a header storage, wherein the header
 storage is configured to provide access to the
 header information in the same order as the frames;
 retrieving header information from the header storage,
15 wherein the header information corresponds to a
 first frame;
 making a routing decision for the first frame based upon
 the header information;
 retrieving the first frame from the receive buffer; and
20 routing the first frame based upon the routing decision.
2. The method of claim 1 wherein the routing decision for
the first frame is made while a preceding frame is being
routed.
- 25 3. The method of claim 1 wherein routing the first frame
comprises transmitting the first frame to the transmit buffer
of a destination determined by the routing decision.
- 30 4. The method of claim 1 further comprising maintaining a
timer corresponding to each header in the header storage.

5. The method of claim 4 further comprising retrieving a timer corresponding to the retrieved header information, determining whether the timer corresponding to the retrieved header information exceeds a predetermined maximum value, and discarding the frame corresponding to the header information if the timer corresponding to the retrieved header information exceeds the predetermined maximum value.

6. The method of claim 1, further comprising snooping on received frames to identify the header information corresponding to each of the frames.

7. The method of claim 1 wherein the receive buffer is a first-in-first-out (FIFO) buffer having a head position and a tail position, wherein entries are written to the tail position and are promoted through the FIFO buffer to the head position, and wherein retrieving the first frame from the receive buffer comprises reading the frame at the head position.

8. The method of claim 7 further comprising providing a bypass circuit coupled to the header storage, wherein if no header information is available at the head of the header storage, the bypass circuit makes next-received header information immediately available.

9. A frame buffer system comprising:

a receive buffer configured to store a plurality of
received frames, wherein the receive buffer is
configured to be accessed in first-in-first-out
fashion;

a header storage configured to store header information
corresponding to each of the frames in the receive
buffer;

transfer logic coupled to the receive buffer and header
storage, wherein the transfer logic is configured to
make a routing decision for each of the frames in
the receive buffer based on the corresponding header
information in the header storage and to transmit
each of the frames to a destination port according
to the corresponding routing decision.

10. The frame buffer system of claim 9 further comprising a
snooping circuit coupled to the header storage, wherein the
snooping circuit is configured to identify header information
in the received frames and copy the corresponding header
information to the header storage.

11. The frame buffer system of claim 9 further comprising a
bypass circuit configured to receive first header information,
wherein when header information is received, if no preceding
header information is currently stored in the header storage,
the bypass circuit is configured to make the first header
information available to the transfer logic.

12. The frame buffer system of claim 9 wherein the header
storage is a first-in-first-out (FIFO) buffer having a head
position and a tail position, wherein header information
entries are written to the tail position and are promoted
5 through the FIFO buffer to the head position, and wherein the
header information at the head position of the FIFO buffer is
available to the transfer logic.

13. The frame buffer system of claim 9 wherein the header
10 storage is a random access memory which is accessed via a head
pointer which indicates a head position and a tail pointer
which indicates a tail position, wherein header information is
written to the tail position and are retrieved from the head
position, and wherein the head and tail pointers are
15 manipulated to promote header information in the header
storage from the tail position to the head position, thereby
providing circular, first-in-first-out operation of the random
access memory.

14. The frame buffer system of claim 9 wherein the receive
20 buffer is a random access memory which is accessed via a head
pointer which indicates a head position and a tail pointer
which indicates a tail position, wherein frames are written to
the tail position and are retrieved from the head position,
25 and wherein the head and tail pointers are manipulated to
promote frames in the receive buffer from the tail position to
the head position, thereby providing circular, first-in-first-
out operation of the random access memory.

15. The frame buffer system of claim 9 further comprising a plurality of timers associated with the each frame in the receive buffer, wherein each timer indicates the amount of time the corresponding frame has been in the receive buffer.

5

16. The frame buffer system of claim 15 wherein the timers are stored in a first-in-first-out (FIFO) timer storage, wherein the timers are promoted through the FIFO timer storage as the corresponding frames are promoted through the receive buffer.

10

17. The frame buffer system of claim 15 wherein the timers are stored in a random access timer storage, wherein each timer is associated with one of the frames in the receive buffer.

15

18. The frame buffer system of claim 9 further comprising a transmit timers associated with the transmit buffer, wherein the transmit timer indicates the amount of time the frame currently residing in the transmit buffer has been in the transmit buffer.

20

19. A switch comprising:

a plurality of ports,

wherein at least one of the plurality of ports is
configured to receive frames for routing to
others of the plurality of ports

wherein the at least one port includes

a receive buffer configured to store a
plurality of frames,

a header buffer configured to store header
information corresponding to the frames
stored in the receive buffer,

transfer logic coupled to the receive buffer
and the header buffer, wherein the
transfer logic is configured to receive
first header information from the header
buffer and to make a routing decision
based upon the received header information
for a frame in the receive buffer
corresponding to the header information.

20. The switch of claim 19 further comprising a dedicated
register coupled to the header buffer and the transmit logic,
wherein the dedicated register is configured to store the
first header information and wherein the transfer logic is
configured to read the first header information from the
dedicated register.


21. The switch of claim 19 wherein the first header
information corresponds to a first frame in the receive buffer
and wherein the transfer logic is configured to make the
routing decision for the first frame prior to the first frame
reaching a head position in the receive buffer.

22. The switch of claim 19 wherein the first header
information corresponds to a first frame in the receive buffer
and wherein the transmit logic is configured to make the
routing decision for the first frame while a preceding frame
is being transferred from the receive buffer.

23. The switch of claim 19 wherein the one of the ports to
which the one of the frames is transferred comprises
a transmit buffer,
a header register and
transmit logic,
wherein the transmit buffer is configured to receive the
one of the frames from the receive buffer and to
store the one of the frames for transmission to a
destination, wherein the header register is
configured to store header information corresponding
to the one of the frames, and wherein the transmit
logic is coupled to the transmit buffer and the
header register and is configured to read the header
information in the header register and to transmit
the one of the frames from the transmit buffer to
the destination based on the header information.

ABSTRACT

A system and method for storing header information in parallel with corresponding frames of data, wherein the frames of data are stored in a first-in-first-out buffer and wherein the header information is accessed to make routing decisions for the frames of data while avoiding having to read the frames out of the buffer. In one embodiment, this buffer system is implemented in a port of a network switch. Receive logic in the port stores frames of data in the storage elements of a FIFO buffer and concurrently snoops on the frame data to obtain header information. The header information is stored in a buffer separate from the FIFO that stores the frames. The header information can be read from the header buffer rather than the frame buffer. A routing decision for each frame can be made before a previous frame is completely read out of the frame FIFO, hence before the corresponding frame is ready to be transmitted. A timer may also be associated with each header in the header buffer so that it can be determined when frames are stale and must be discarded.



PRIOR ART

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6



**DECLARATION FOR
UTILITY OR DESIGN
PATENT APPLICATION
(37 CFR 1.63)**

Attorney Docket No.

CROSS1400-1

First Named Inventor

Michael A. Nelson, et al.**COMPLETE IF KNOWN**

Filing Date

Application Number

Group Art Unit

Examiner

Declaration Submitted
with Initial FilingDeclaration Submitted after
Initial Filing**As a below named inventor, I hereby declare that:**

My residence, post office address, and citizenship are as stated below to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

SYSTEM AND METHOD FOR STORING FRAME HEADER DATA

(Title of Invention)

the specification of which was filed on (MM/DD/YYYY)

as United States Application Number of PCT International
Application Number

and was amended on (MM/DD/YYYY) (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I hereby state I do not know and do not believe that said invention, design or discovery was ever known or used in the United States of America before my invention or discovery thereof, or patented or described in any printed publication in any country before my invention or discovery thereof, or more than one year prior to this application, or in public use or on sale in the United States of America more than one year prior to this application; that said invention, design or discovery has not been patented or made the subject of an inventor's certificate issued prior to the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns; and that I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me which is material to the patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached? YES	NO

Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below:

Application Number(s)	Filing Date (MM/DD/YYYY)	
60/202,836	05/08/00	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto

DECLARATION -- Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States Application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) associated with **Customer ID No. 25094** to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

Given Name (first and middle [if any])

Family Name or Surname

Michael A.

Nelson

Inventor's Signature

Date

10/18/00

Residence Address

4213 Southwest Huber Street

Citizenship

United States

City

Portland

State

OR

Zip

97219

Country

United States

Post Office Address

same

Name of Additional Inventor:

Given Name (first and middle [if any])

Family Name or Surname

Thomas W.

Bucht

Inventor's Signature

Date

10/18/2000

Post Office Address

18655 Camelot Lane

Citizenship

United States

City

Hillsboro

State

OR

Zip

97123

Country

United States

Post Office Address

same

Name of Additional Inventor:

Given Name (first and middle [if any])

Family Name or Surname

Inventor's Signature

Date

Residence: City

State

County

Citizenship

Post Office Address

Post Office Address

City

State

Zip

Country

Direct all correspondence to Customer ID No. 25094:

Name

Mark L. Berrier

Address

City

State

Zip

Country

Telephone

(512) 457-7016

Fax

(512) 457-7070

V\U\4044948.1
103671-991401